TOPAZ COMPACT VALVE PRODUCT INFO [COMPACT] PROTVALVE

Description


Topaz compact float valves are float operated valves for use in the automatic filling of water troughs, tanks & cisterns where space is limited. The valve is configured for above water mounting only. The compact weighted float operates a small pilot valve which in turn operates the main diaphragm valve. Topaz Compact float valves are positive on/off and are ideal when working with pump supplied water in a small compartment.

Applications

Maintaining Water Levels in:


- Animal Drinking Troughs
- Water Storage Tanks
- Water Cisterns
- Air Conditioning Systems
- High Pressure Cleaning Systems
- Irrigation Applications

Flow Graph



Compact Weighted Float

- High flow
- Compact robust construction
- Made from corrosion
 resistant materials
- Shuts down slowly to minimise water hammer
- 20 60mm (3/4" 2 1/2") water level differential (increases as water inlet pressure increases)
- Pressure rating 0.3 10 Bar (5 - 150 PSI)
- Float position easily adjustable with no tools
- Valve has switch to lock it in off position
- Has port to connect Frostpro anti freeze device
- Detach[™] Valve Seal Access System for quick access to valve seal



Opti	ons	5							
	BSP				NPT				Thread size
Inlet Size	1⁄2″	3⁄4″	1″	1 ¼″	1⁄2″	3⁄4″	1″	1 ¼″	
Detach Base Short Tail		~	✓	~		✓	~		
Detach Base Long Tail	~	~	1	1	~	1	1		Detach
Long Tail	: Sup	plied v	vith ba	acknut	and s	eal wa	isher.		
Floats: 55mm wide float supplied standard.						Compact Float			
N.B. (No c	ther fl	oat is	compa	atible v	with th	nis valv	ve)		
、 、									55mm

TOPAZ TROUGH VALVE SPECIFICATION

PRODUCT	DDUCT CODE INLET SIZE		CODE		OPTIONS	CODE	
Topaz Compact	TPVC		BSP	NPT	Detach Base	D	
Float Valve		1/2″	15	0050	Long Tail Thread	LT	
		3/4″	20	0075			
		1″	25	0100			
		1 ¼″	32	0125			


NOTE: If no options are specified the standard ones will be supplied

Note: Product may differ slightly from these specs due to ongoing product development.

TOPAZ COMPACT VALVE DIMENSIONS & MATERIALS







ſ	Float Dir	(Tail Dimensions			
	2 ¼″ 56mm	4 1⁄8″ 104mm	Dimension A	mm	inches
			20mm (3/4") Short tail 25mm (1") bsp/npt short tail 32mm (1 1/4") bsp/npt short tail	22 22 25	7% 7% 1
3 ½″ 91mm		JOBE Valves jobevalves.com	15mm (1/2") long tail 20mm (3/4") long tail 25mm (1") bsp/npt long tail 32mm (1 1/4") bsp/npt long tail	100 38 54 60	4 1 ½ 2 ⅛ 2 ⅔

Part	Material	Part	Material
Valve Body & Tail	Glass Filled Nylon	Springs, Bolts, Nuts,	304 Stainless Steel
White & Yellow	Acetal	Pin, Screws	
Internal Parts		O'Rings	Nitrile
Filter	PP/Nylon	Float	HDPE
Diaphragm	EPDM	Actuator / Arms &	ABS
Seal	TPU	Caps	
Float Cord	Polyester		

Maximum Operating Temperature

60°C, 140°F

TOPAZ COMPACT FLOAT VALVE PARTS IDENTIFICATION SHEET





